



Mobil Delvac Legend™ 20W-50 Standard Defense

Mobil Commercial Vehicle Lube , Thailand

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Legend™ 20W-50 Standard Defense is a high performance, heavy duty engine oil that provides proven protection to diesel engines operating in severe on and off-highway service applications. Mobil Delvac Legend 20W-50 Standard Defense is recommended by ExxonMobil for use in a wide range of heavy duty applications and operating environments found in the trucking, construction, and agricultural industries. It is also suitable for gasoline engines.

This product is fully compatible with Mobil Delvac Super 20W-50 and can be used as a replacement of same.

Features and Benefits

The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Stay-in-grade shear stability	Helps reduce oil consumption and wear

Applications

Recommended by ExxonMobil for use in:

- Diesel-powered equipment from leading diesel engine manufacturers.
- On highway light and heavy duty trucking.
- Off highway industries including: trucking, construction, quarrying and agriculture.
- Mixed diesel/gasoline engine fleets.

Specifications and Approvals

This product is recommended for use in applications requiring:
API CF-4
API SF
API SG

Properties and Specifications

Property	

Property	
Grade	SAE 20W-50
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	149
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	17.6
Pour Point, °C, ASTM D97	-30
Ash, Sulfated, mass%, ASTM D874	0.97
Flash Point, °C, ASTM D92	220
Density @ 15 C, g/cm ³ , ASTM D4052	0.88

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2022

ExxonMobil Marketing (Thailand) Limited

3195/26, 22nd Floor, Rama IV Road

Klong Ton, Klong Toey District

Bangkok 10110

Thailand


+66 2 407 4000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved