



Mobil Super™ Everyday Protection Turbospeed 15W-40

Mobil Passenger Vehicle Lube , Thailand
Premium Passenger Vehicle Diesel Engine Oil

Product Description

Mobil Super™ Everyday Protection Turbospeed 15W-40 is a high performance diesel engine oil that provides excellent lubrication of today's diesel engines promoting extended engine life. The product is designed to provide a high level of performance and protection under everyday conditions.

Features and Benefits

Mobil Super™ Everyday Protection Turbospeed 15W-40 is engineered for today's tougher engine specifications and provide:

- Improved soot handling and oxidation capability for excellent wear protection and engine cleanliness
- Improved engine quietness compared with lower viscosity oils

Applications

Mobil Super™ Everyday Protection Turbospeed 15W-40 is suitable for nearly all diesel engine types including common rail, turbocharged and intercooler models. ExxonMobil recommends for the following vehicle types and conditions:

- Latest engine technologies
- Diesel engines in passenger cars, SUVs, MPVs and vans
- Highway cruising
- Normal Operating Conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:	
API CG-4	

This product meets or exceeds the requirements of:	
API CI-4	
API CH-4	
API SL	

Properties and Specifications

Property	
Grade	SAE 15W-40

Property	
Viscosity Index, ASTM D2270	133
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.3
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	109
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	4.1
Mini-Rotary Viscometer, Apparent Viscosity, -25 C, mPa.s, ASTM D4684	18100
Ash, Sulfated, mass%, ASTM D874	1.3
Flash Point, Cleveland Open Cup, °C, ASTM D92	223
Pour Point, °C, ASTM D97	-33
Density @ 15 C, kg/l, ASTM D4052	0.88
Total Base Number, mgKOH/g, ASTM D2896	10.4

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2022
ExxonMobil Marketing (Thailand) Limited
3195/26, 22nd Floor, Rama IV Road
Klong Ton, Klong Toey District
Bangkok 10110
Thailand

+66 2 407 4000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved